



## NECKEL CAN

	INTERNATIONAL STANDARD	RANDOM SAMPLE	50PCS
COMPOUND EDGE WIDTH	2.50 ± 0.19mm	2.36 ~ 2.51 mm	
SEALING BOTTOM HEIGHT	70.50 ± 0.30mm	70.50 ~ 70.66mm	
REEL SEAL WIDTH	2.80 ± 0.19mm	2.61 ~ 2.74 mm	
REEL SEAL THINCKNESS	< 1.34mm	1.25 ~ 1.31mm	
LENGTH OF BODY HOOK	1.85 ± 0.19mm	1.66 ~ 1.80 mm	
COVER HOOK LENGTH	1.85 ± 0.19mm	1.70 ~ 1.90 mm	
OVERLAP LENGTH	> 1mm	1.10 ~ 1.20 mm	
TIGHTNESS	> 50%	75% ~ 85%	
OVERLAP RATE %	> 55% (Projection method)	55% ~ 70%	
CONDUCTIVITY VALUE	SINGLE < 30mA、AVERAGE < 15mA	SINGLE < 10mA、AVERAGE < 2mA	
LEAK TEST	Keep the pressure under 0.18MP air pressure	QUALIFIED	



METAL BEVERAGE CONTAINER OPERATIONS  
9300 W. 108TH CIRCLE

ADD: B805, No 38 .Qinfu Road ,Liuyue Community,  
Henggang Street, Longgang District, Shenzhen  
City, China

#571 X #113/#200  
3.5 OZ

DATE CREATED  
05/07/2021

APPROVED